

EURODAINU

INFLATING, CHECKING AND ADJUSTMENT OF PRESSURE
(passenger cars, motorcycles, trucks and earthmover)



PROTECTION

- Rubber safety protector wrapping the measure system.
- Protected dial with a clipped on transparent.

Available Items:
R 1822-Z : PC-truck, hose L= 1.50 m
38879-58 : PC-truck, L= 3 m
35864-58 : EM, tuyau L= 3 m
38902-58 : EM, L= 6 m
R 1821-Z : Double graduation bar/psi (out EC), hose L= 1.50 mC

HANDLE

Safety pinch-proof handle.
Catephoresis-treated.
Corrosion-resistant.

1/4" female air inlet connector.



Hoses 7 X 13 mm,
Length 1.50 m, 3 m or 6 m.

ROBUSTNESS

Material : IXEF high quality Polyarylamide, glass-fiber reinforced.
Polyarylamide exhibits superior strength and stiffness combined with outstanding surface gloss and exceptional flow.

TECHNICAL ASSISTANCE

provided by Schrader

Graduation :
from 0.7 to 11 BAR
Air or Nitrogen use

RELIABLE

needle anchoring
Very high level of accuracy for measurement that remains precise in case of impact on the device.
Air filtration in the indicator valve core through a micro-porous stainless steel and nickel silver filter.
Device resisting to accidental high pressure of 13.75 bar.

EURODAINU pressure gauges are regulated by:
European Directive 86/217/CEE, Decree 88/87, Norm Afnor NFR 63-302.
Schrader Eurodainu pressure gauges are delivered with a confirmation of examination in a government-approved format.



39766-67

Intermediate-sized nipple for inflating gauges equipped with 1/4" Gaz BSP connected on air inlet



65088-67

Teflon precoated male thread coupler 1/4" Gaz BSP



65089-67

Nipple for hose int Ø 7 mm conical threading 1/4" Gaz BSP

