



UNIV AIR®

INFLATING, CHECKING AND ADJUSTMENT OF PRESSURE
(passenger cars, motorcycles, trucks and earthmover)

HIGH TECHNOLOGY PLASTIC COMPONENTS



Available Items:
 39700-00 : PC-truck, hose L= 1.50 m
 39701-00 : PC-truck, L= 3 m
 39703-00 : EM, L= 6 m
 39702-00 : Double graduation bar/psi (out EC), hose L= 1.50 mC



Conform to 86/217/EC Directive

Graduation :
from 0.7 to 11 BAR
 Air or Nitrogen use

- " female air inlet connector
- Watertight performance reinforced with a clipped on transparent dial.
- Very high level of accuracy for measurement that remains precise in case of impact on the device.
- Robustness: high technology plastic components.
- Safety handle.
- Comfortable handling: the gauge is never cold
- Corrosion resistance thanks to the inside mechanism made of appropriate material.
- Filtration of air in the gauge mechanism with stainless steel and nickel silver micro-porous filters.
- Device resisting to accidental high pressure of 15 bar.



39766-67

Intermediate-sized nipple for inflating gauges equipped with 1/4" Gaz BSP connected on air inlet



65088-67

Teflon precoated male thread coupler 1/4" Gaz BSP



65089-67

Nipple for hose int Ø 7 mm conical threading 1/4" Gaz BSP

TECHNICAL ASSISTANCE
 provided by Schrader